

# Price computing scale KERN RPB



## Retail scale with EC type approval [M] and memory for article prices

### Features

- **1 Elevated display** backlit, revolving on column, height of stand approx. 530 mm, only RPB-HM, must be ordered at purchase
- **2 Second display** on the rear of the balance, standard (only with models without the elevated display)
- **Three displays** for: weight (verifiable), unit price, total price
- **Unit price can be switched** from €/kg to €/100 g
- **Memory (PLU) for 10 article prices**
- **Auto-clear-key:** Unit price entry is automatically set to zero when scale is unloaded

- **3 High mobility** thanks to its rechargeable batteries (optional) and low weight

### Technical data

- Large backlit LCD displays, digit height 20 mm
- Dimensions of weighing plate (stainless steel) WxD 294x225 mm
- Overall dimensions WxDxH 320x350x125 mm
- Net weight approx. 3,9 kg
- Permissible ambient temperature -10 °C / 40 °C

### Application examples:

- retail shops
- market places
- farm shops
- pick your own fruit and vegetable sales

**Note:** In commercial trade, official verification duties exist

### Accessories

- **Protective working cover** standard, can be reordered, KERN CFS-A02, **€ 25,-**
- **Rechargeable battery pack internal**, operating time approx. 80 h without back-light, charging time approx. 14 h (internal charging with mains adapter). AUTO-OFF function to preserve the battery, can be switched off. Charge condition indicator using three-colour LED, KERN GAB-A04, **€ 40,-**
- **Tare pan made from stainless steel**, ideal for weighing loose fruit and vegetables, WxDxH 370x240x20 mm, KERN RFS-A02, **€ 45,-**

#### STANDARD



#### OPTION



#### FACTORY



Model	Weighing range [Max] kg	Read-out [d] g	Verific. value [e] g	Minimum load [Min] g	Reproducibility g	Linearity g	Price excl. of VAT ex works €	Options			
								Verification		DKD Calibr. Certificate	
KERN								KERN	€	DKD KERN	€
<b>Dual-range balance (D=Dual):</b> switches automatically to the next largest weighing range [Max] and readout [d]											
RPB 6K1DM	3   6	1   2	1   2	20	1   2	± 1   ± 2	205,-	965-228	50,-	963-128	80,-
RPB 15K2DM	6   15	2   5	2   5	40	2   5	± 2   ± 5	205,-	965-228	50,-	963-128	80,-
RPB 30K5DM	15   30	5   10	5   10	100	5   10	± 5   ± 10	205,-	965-228	50,-	963-128	80,-
with elevated display											
RPB 6K1DHM	3   6	1   2	1   2	20	1   2	± 1   ± 2	230,-	965-228	50,-	963-128	80,-
RPB 15K2DHM	6   15	2   5	2   5	40	2   5	± 2   ± 5	230,-	965-228	50,-	963-128	80,-
RPB 30K5DHM	15   30	5   10	5   10	100	5   10	± 5   ± 10	230,-	965-228	50,-	963-128	80,-

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.